



Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: YO-30M855/-----
Product name: WB TOP COAT, INTERIOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: WB TOP COAT, INTERIOR

1.3. Details of the supplier of the safety data sheet

Name: **RENNER ITALIA S.p.A.**
Full address: **Via Ronchi Inferiore, 34**
District and Country: **40061 Minerbio BO**
Italia
Tel. **+39 051-6618211**
Fax **+39 051-6606312**

e-mail address of the competent person responsible for the Safety Data Sheet: **sds@renneritalia.com**

Product distribution by:

1.4. Emergency telephone number

For urgent inquiries refer to

RENNER ITALIA S.p.A. - Tel. +39 051-6618211 (dal lunedì al venerdì dalle 8.30 - 13.00 e dalle 14.00 - 17.30)
ITALIA
Centro antiveleni Milano - Tel. +39 02-66101029
Centro antiveleni Firenze - Tel. +39 055-7947819
CROATIA
Služba za izvanredna stanja (112)
Centar za kontrolu otrovanja (01/2348-342)
HUNGARY
Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ)
1096 Budapest, Nagyvárad tér 2.
Telefon: +36 1 476 6464 (8-16 óráig), +36 80 201 199 (éjjel-nappal hívható) magyar nyelven
LATVIA
Valsts ugunsdzesibas un glabšanas dienests: (+371) 112
Saindešanas un zalu informacijas centrs: (+371) 67042473 (visu diennakti)
LITHUANIA
Apsinuodijimų kontrolės ir Informacijos biuras visą parą tel. (8 5) 236 2052
Bendras pagalbos telefonas: 112
NORWAY
Emergency number: 113
POLSKA
Numer telefonu alarmowego: +48 22 615 27 51
PORTUGAL
Centro de Informação Anti-Venenos: +351 808 250 143
BULGARIA - България
Национален център по токсикология, МБАЛСМ "Пирогов"
телефон: +359 2 9154 233

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

**SECTION 2. Hazards identification ... / >>**

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210

Safety data sheet available on request.

EUH208

Contains:

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one

methyl- 2H- isothiazol- 3-one (3:1)

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)

propionyloxypoly(oxyethylene)

May produce an allergic reaction.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.1. Substances**

Information not relevant

3.2. Mixtures

Contains:

Identification **x = Conc. %** **Classification 1272/2008 (CLP)****2-(2-BUTOXYETHOXY)ETHANOL**

CAS 112-34-5 1,5 ≤ x < 2,5 Eye Irrit. 2 H319

EC 203-961-6

INDEX 603-096-00-8

Reg. no. 01-2119475104-44-XXXX

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)**propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-****4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)****propionyloxypoly(oxyethylene)**

CAS 400-830-7 0,5 ≤ x < 1 Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC 607-176-00-3

INDEX 607-176-00-3

Reg. no. 01-0000015075-76-xxxx

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one**methyl- 2H- isothiazol- 3-one (3:1)**CAS 55965-84-9 0 ≤ x < 0,0015 Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314,
Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10

EC

INDEX 613-167-00-5

Reg. no. 01-2120764691-48-xxxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.



SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**SECTION 6. Accidental release measures ... / >>****6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
DNK	Danmark	Graensevaerdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	DĖL LIETUVOS HIGIENOS NORMOS HN 23:2007 CHEMINIŲ MEDŽIAGŲ 2007 m. spalio 15 d. Nr. V-827/A1-287
LVA	Latvija	Ķīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā 2012
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 20. júna 2007
SVN	Slovenija	Uradni list Republike Slovenije 15. 6. 2007
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
EU	OEL EU	Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2016

**SECTION 8. Exposure controls/personal protection ... / >>****DIETHYLENE GLYCOL MONOETHYL ETHER****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	SWE		15		30

Predicted no-effect concentration - PNEC

Normal value in fresh water	1,98	mg/l
Normal value in marine water	0,198	mg/l
Normal value for fresh water sediment	7,32	mg/kg
Normal value for marine water sediment	0,732	mg/kg
Normal value of STP microorganisms	500	mg/l
Normal value for the food chain (secondary poisoning)	444	mg/kg
Normal value for the terrestrial compartment	0,34	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				50				mg/kg bw/d
Inhalation			18	37			30	61
			mg/m3	mg/m3			mg/m3	mg/m3
Skin				25				83
				mg/kg bw/d				mg/kg bw/d

**SECTION 8. Exposure controls/personal protection ... / >>****Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,2				INHAL
MV	SVN	0,05				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00339	mg/l
Normal value in marine water	0,00339	mg/l
Normal value for water, intermittent release	0,00339	mg/l
Normal value of STP microorganisms	0,23	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,11 mg/kg bw/d		0,09 mg/kg bw/d				
Inhalation	0,02 mg/m3		0,04 mg/m3		0,04 mg/m3		0,02 mg/m3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

Take the normal precautions for handling chemicals and apply an adequate standard of workplace hygiene.

Users must assess the risks in their workplace and adopt:

- Primary collective protective measures such as adequate natural ventilation and local extraction
- Personal protective equipment to manage the combination of residual risks

Personal protective equipment varies according to the possible exposure and hazardousness of the working conditions, so the final choice depends on the risk assessment.

HAND PROTECTION

Use category III chemical resistant gloves according to the EN 374 standard

Brief contact (splash protection) – non-exhaustive list

Suitable material: NITRILE RUBBER (NBR)

Glove thickness: greater than 0.4 mm

Breakthrough time: from 30 to 60 minutes

Breakthrough index: at least 2

The gloves must be replaced if there are signs of deterioration. In any case, users must assess the risks to determine the most suitable type of glove for the conditions of use.

SKIN PROTECTION

Wear work clothes and safety footwear that complies with EN ISO 20344

EYE PROTECTION

Wear safety glasses (EN 166).

RESPIRATORY PROTECTION

Use a mask with EN140 and/or EN136 approval, with an ABEK type filter (EN 14387)

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

NOTE: Determination of the flash point may be NA (not applicable), the product being non flammable.

9.1. Information on basic physical and chemical properties

Appearance viscous liquid

**SECTION 9. Physical and chemical properties ... / >>**

Colour		milky
Odour		Typical
Odour threshold		Not available
pH		7,5-8,5
Melting point / freezing point		Not available
Initial boiling point	>	65 °C
Boiling range		Not available
Flash point	>	Not applicable
Evaporation speed		Not available
Flammability (solid, gas)		not applicable
Lower inflammability limit		Not available
Upper inflammability limit		Not available
Lower explosive limit		Not available
Upper explosive limit		Not available
Vapour pressure		Not available
Vapour density		Not available
Relative density		1,03
Solubility		soluble in water
Partition coefficient: n-octanol/water		Not available
Auto-ignition temperature		Not available
Decomposition temperature		Not available
Viscosity		Not available
Explosive properties		not applicable
Oxidising properties		not applicable

9.2. Other information

Total solids (250°C / 482°F)	31,65 %	
VOC (Directive 2010/75/EC) :	2,86 % - 29,45	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

DIETHYLENE GLYCOL MONOETHYL ETHER

DIETHYLENE GLYCOL MONOETHYL ETHER - it can form explosive mix with air in presence of high temperature (T> 94°C)

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

10.5. Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	Not classified (no significant component)
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	Not classified (no significant component)

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Oral)	2410 mg/kg
LD50 (Dermal)	2764 mg/kg

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)

LD50 (Oral)	66 mg/kg
LD50 (Dermal)	141 mg/kg
LC50 (Inhalation)	0,17 mg/l/4h

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)

LD50 (Oral)	> 5000 mg/kg Rat
LD50 (Dermal)	> 2000 mg/kg Rat
LC50 (Inhalation)	> 5,8 mg/l 4 h Rat

DIETHYLENE GLYCOL MONOETHYL ETHER

LD50 (Oral)	6031 mg/kg
LD50 (Dermal)	9143 mg/kg
LC50 (Inhalation)	0,02 mg/l 8 h

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

**SECTION 11. Toxicological information** ... / >>RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity**2-(2-BUTOXYETHOXY)ETHANOL**

LC50 - for Fish 1300 mg/l/96h *Lepomis macrochirus*
EC50 - for Crustacea > 100 mg/l/48h *Daphnia magna*

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one

methyl- 2H- isothiazol- 3-one (3:1)

LC50 - for Fish 0,188 mg/l/96h *Oncorhynchus mykiss*
EC50 - for Crustacea 0,16 mg/l/48h *Daphnia magna*
EC50 - for Algae / Aquatic Plants 0,0052 mg/l/72h *Skeletonema costatum*
Chronic NOEC for Fish 0,098 mg/l *Oncorhynchus mykiss* (28 d)
Chronic NOEC for Crustacea 0,004 mg/l *Daphnia magna* (21 d)
Chronic NOEC for Algae / Aquatic Plants 0,0012 mg/l *Skeletonema costatum*

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)

LC50 - for Fish 2,8 mg/l/96h *Oncorhynchus mykiss*
EC50 - for Crustacea 4 mg/l/48h *Daphnia magna*
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h *Pseudokirchneriella subcapitata*
EC10 for Algae / Aquatic Plants 10 mg/l/72h *Pseudokirchneriella subcapitata*

**SECTION 12. Ecological information ... / >>**

DIETHYLENE GLYCOL MONOETHYL ETHER
LC50 - for Fish 6010 mg/l/96h
EC50 - for Crustacea 1982 mg/l/48h Daphnia magna

12.2. Persistence and degradability

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly biodegradable

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)
NOT rapidly biodegradable

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-
4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
propionyloxypoly(oxyethylene)
NOT rapidly biodegradable

DIETHYLENE GLYCOL MONOETHYL ETHER
Rapidly biodegradable > 80%

12.3. Bioaccumulative potential

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: n-octanol/water 1

reaction mass of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
propionyl- ω -hydroxypoly(oxyethylene); α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-
4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
propionyloxypoly(oxyethylene)
Partition coefficient: n-octanol/water 3,6
BCF 502 h Oncorhynchus mykiss

DIETHYLENE GLYCOL MONOETHYL ETHER
BCF < 100

12.4. Mobility in soil

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: soil/water 10

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

For disposal or recovery in EU countries, use the relevant waste code (EWC code) identified in the European Waste Catalogue. The producer of the waste must assign the EWC code according to the sector and type of process. Disposal must be carried out by an authorised waste management company.

After the producer of the waste has assigned the EWC code, the contaminated packaging must be sent for recovery or disposal in compliance with the European waste management regulations. Disposal must be carried out by an authorised waste management company.

For waste disposal or recovery in countries outside the EU, comply with the national or local regulations in force. For disposal or recovery of contaminated packaging in countries outside the EU, comply with the national or local regulations in force.

**SECTION 15. Regulatory information ... / >>****15.2. Chemical safety assessment**

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament



SECTION 16. Other information ... / >>

6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

03 / 07 / 09 / 15.